

Quick reference manual
for the SPHInX DFT program

Christoph Freysoldt, freysoldt@mpie.de

August 21, 2017



Contents

1	Introduction	3
1.1	About	3
1.2	sphinx invocation	3
1.3	Units	3
2	The SPHInX parser	3
2.1	Overview	3
2.2	Expressions	4
2.3	Included files	5
2.4	The format statement, std files.	5
3	Overview on the input file for DFT calculations	5
3.1	The <code>structure</code> group	6
3.1.1	The <code>species</code> group	7
3.1.2	The <code>atom</code> group	8
3.1.3	<code>symmetry</code> group	8
3.2	The <code>basis</code> group	9
3.2.1	The <code>kPoint</code> group	10
3.2.2	The <code>kPoints</code> group	10
3.2.3	The <code>from</code> group	11
3.2.4	The <code>to</code> group	11
3.3	The <code>pawPot</code> group	12
3.4	The <code>PAWHamiltonian</code> group	13
3.4.1	The <code>vExt</code> group	14
3.4.2	The <code>xcMesh</code> group	14
3.5	The <code>spinConstraint</code> group	14
3.6	The <code>initialGuess</code> group	15
3.6.1	The <code>waves</code> group	16
3.6.2	The <code>lcao</code> group	16
3.6.3	The <code>rho</code> group	16
3.6.4	The <code>atomicSpin</code> group	17
3.6.5	The <code>charged</code> group	18
3.6.6	The <code>occupations</code> group	18
3.6.7	The <code>exchange</code> group	19
3.7	The <code>pseudoPot</code> group	19
3.8	The <code>PWHamiltonian</code> group	20
3.9	The <code>main</code> group	21
4	Electronic loop	22
4.1	<code>scfDiag</code> : iterative diagonalization + density mixing	22
4.1.1	The <code>CCG</code> group	25
4.1.2	The <code>blockCCG</code> group	25
4.1.3	The <code>preconditioner</code> group	26
4.2	<code>CCG</code> : direct minimization	27

5	Geometry optimizers	28
5.1	The QN group	28
5.1.1	The bornOppenheimer group	29
5.2	The linQN group	29
5.3	The ricQN group	30
5.3.1	The ric group	31
5.4	The extControl group	32
6	Output	33
6.1	energy.dat: total energies	33
6.2	residue.dat: density residues	34
6.3	eps.dat: eigenvalues	34
6.4	rho.sxb: density (binary)	34
6.5	waves.sxb: wave functions (binary)	34
6.6	relaxedStr.sx: final atomic structure	34
6.7	relaxHist.sx: geometry optimization history	34
6.8	energy-structOpt.dat: geometry optimization energies	34
6.9	ftwisdom.dat: FFTW plans	35
	Index	36

1 Introduction

1.1 About

SPHInX is a C++ programming library for developing efficient physics codes. Its dominant feature is a plane-wave density-functional theory (DFT) code named `sphinx`. This document is a short, non-tutorial manual for the DFT program `sphinx`. Other features of `sphinx` are not described here. In particular, $\mathbf{k} \cdot \mathbf{p}$, EXX, and tight-binding, are not covered.

1.2 `sphinx` invocation

`sphinx` reads its input from a main input file, usually called ‘`input.sx`’. Its format is described in Sec. 3. `sphinx` produces output in several dedicated files (see Sec. 6), but the main output comes on stdout (i.e. the screen). `sphinx` can be asked to duplicate (or redirect) its output into a log file. `sphinx` – like all SPHInX executables – can take options on the command line that control some of its global behavior.

Option	argument	description
<code>--help</code>		show all the available options
<code>--log</code>		create a log file
<code>--quiet</code>		don't produce output on stdout
<code>--input</code>	filename	input file (default: <code>input.sx</code>)

If SPHInX has been compiled with the FFTW library for the fast Fourier transforms (FFTs), there are two additional options to access the planning mode of FFTW (`--fastfft` and `--wisdom`).

1.3 Units

SPHInX uses mostly atomic units: bohr for coordinates, Hartree atomic units for energies. Some exceptions exist, e.g. for plane-wave cutoffs (Rydberg), electronic temperature (eV), eigenvalues (eV), ...

2 The SPHInX parser

2.1 Overview

The input file format is best explained starting from an **example**:

```

basis {
  eCut   = 20; // Ry
  kPoint {
    coords = [1/2,1/2,1/2];
    weight = 1;
    relative;
  }
  folding = 4 * [1,1,1];
}

```

The SPHInX input format is a structured, hierarchical format with a C-like syntax. It consists of named groups and parameters. Parameter and group names are case-sensitive.

Groups. The content of a **group** (such as **basis**) is enclosed in curly brackets `{}`. Groups may contain parameters, and other groups.

The order of unique groups is *not* important. Groups that may appear multiple times, or groups that describe an action of the code (notably in the **main** group) are processed in the order of appearance.

Parameters. **Parameters** (such as **eCut**) are assigned values with the equal sign. Parameter assignments must be followed by a semicolon (`;`). Some parameters/variables may be a vector (or a list), for instance **coords** in the example above. The vector elements are comma-separated and enclosed by square brackets `[]`. Parameters may expect string values. The string is enclosed in double quotes (`"`). Parameters that expect filenames may be enclosed by `<>` to look for the files in the search path. Enclosure by double quotes looks for them in the current directory.

Flags. Flags are special parameters, that normally do not carry a value. A flag (e.g. **relative**) is set by specifying its name, followed by a semicolon. Flags are unset by assigning the value 0.

White space. White space (including tabs and newlines) can be added quite freely, except within words, numbers, etc.

Comments. **Comments** can be added by the `//` and `/* */` syntax. A `//` comment extends until the rest of the line.¹ A `/* */` comment omits everything between the `/*` and `*/` markers.

2.2 Expressions

The SPHInX parser supports basic algebraic expressions, such as adding, subtracting, multiplying etc. All numbers are changed to double precision when

¹Instead of `//` one can also use `#` (like in shell) or `%` (like in LaTeX).

doing so, i.e., $1/2$ is equivalent to 0.5 . Some mathematical functions (`sqrt`, `cbrt` (cubic root), `sin`, `cos`, `exp`, `log`) are available. At the top level, additional variables may be set and used in algebraic expressions. Strings can be concatenated with `+`.

2.3 Included files

The input file may include other files via the `include` statement.

```
include <parameters.sx>;  
include "startStructure.sx";
```

Similar to C/C++, double quotes indicate that the file is expected in the current directory (of execution), while `<>` indicates to look for the file in the parser's search path. The file `parameters.sx` (located in `share/sphinx/`) contains a large number of predefined keys that may offer mnemonic names for some (numeric) settings. It should always be included.

2.4 The format statement. std files.

Each input file should begin with a `format` statement, e.g. for PAW

```
format paw;
```

What is the role of this statement? The SPHInX input file is read by the SPHInX parser, and validated against a syntax type definition (`std`). The relevant `std` file is selected by the `format` statement in the input file (here, it would load `'paw.std'`). The `std` files are located² in `share/sphinx/std/`. The `std` files themselves have a similar format as the actual input file, but define the type expected for each parameter, as well as mutual exclusions, range limits, etc. The `std` files can be an additional resource for discovering what SPHInX offers. The `std` files make heavy use of the `include` feature.

3 Overview on the input file for DFT calculations

A typical input file for PAW will look like this:

²within the `sphinx/src` folder in the source tree, and within the installation path when installed

```

format paw;
include <parameters.sx>;

structure { ... }
basis { ... }
pawPot { ... }
PAWHamiltonian { ... }
initialGuess { ... }
main { ... }

```

The individual groups are described in the other sections of this manual. They define the atomic structure (**structure**), the plane-wave basis set and **k**-points (**basis**), the PAW potentials to be used (**pawPot**), other settings of the PAW Hamiltonian such as the xc functional (**PAWHamiltonian**), how to set up the starting density and wavefunctions (**initialGuess**), as well as the type of calculation (geometry optimization, single-point calculation, band structure, ...) in the **main** group.

A typical input file for norm-conserving pseudopotentials will look like this:

```

format sphinx;
include <parameters.sx>;

structure { ... }
basis { ... }
pseudoPot { ... }
PWHamiltonian { ... }
initialGuess { ... }
main { ... }

```

Quite similar, no? The difference is in the format, the **pseudoPot** and **PWHamiltonian** groups.

3.1 The structure group

The structure group specifies the atomic positions in SPHInX format.

Example:

```

structure {
  cell = 10.2 * [[0, 1/2, 1/2],
                 [1/2, 0, 1/2],
                 [1/2, 1/2, 0]];

  species {
    element="Si ";
    atom { coords = [0,0,0]; relative; }
    atom { coords = [1/4,1/4,1/4]; relative; }
  }
}

```

The following parameters may be set:

parameter	description
movable	(flag) allow atoms to move. Default: all atoms are movable, unless any movable flag is used for any species/atom.
movableX	(flag) allow atoms to move in the x direction. Default: movable, unless movableY or movableZ are used.
movableY	(flag) allow atoms to move in the x direction. Default: movable, unless movableX or movableZ are used.
movableZ	(flag) allow atoms to move in the x direction. Default: movable, unless movableX or movableY are used.
cell	(required) The unit cell (in bohr). This is a list of the three basis vectors in Cartesian coordinates.

The **movable** flags are applied hierarchically. Settings at the structure level can be overridden at the species or atom level. Disabling a movable flag of a surrounding group is achieved by setting to 0, e.g. **movableY** = 0;

The **structure** group must contain at least one **species** group. It may contain a **symmetry** group.

3.1.1 The species group

The **species** group defines atomic positions for one chemical species. Atoms must be sorted by their chemical species.


```

species {
  element="Al ";
  atom { ... }
  atom { ... }
}
species {
  element="O ";
  atom { ... }
  atom { ... }
  atom { ... }
}

```

The `species` group may contain the `movable`, `movableX`, `movableY`, `movableZ` parameters as specified above. In addition it may contain the `element` parameter to indicate the chemical symbol, enclosed by double quotes.

The `species` group must contain at least one `atom` group.

3.1.2 The atom group

The `atom` group defines atomic positions for one atom. Atoms must be sorted by their chemical species.

The `atom` group may contain the `movable`, `movableX`, `movableY`, `movableZ` parameters as specified above in Sec. 3.1. In addition, the following parameters may be set:

parameter	description
<code>coords</code>	(required) The atomic coordinates as a 3-vector. Unless the <code>relative</code> flag is employed, the coordinates are Cartesian (in bohr).
<code>relative</code>	(flag) The coordinates are given relative to the unit cell vectors.
<code>movableLine</code>	(optional) The movement of the atom is restricted to a line. The value gives the direction of the line as a 3-vector.
<code>label</code>	(optional string) Assign a label (or rather a tag) to this atom. If labels are used, atoms with different labels are considered inequivalent. Think of spin configurations for a use-case.

3.1.3 symmetry group

The `symmetry` group (within the structure group) defines the rotational symmetries of the system around the origin of the coordinate system. If not given, the symmetries are determined automatically. However, non-chemical degrees of freedom (such as spins) may break the symmetry. As all forces / displacements are symmetrized, such a situation may require to set the symmetries

by hand. Alternatively, **giving an empty symmetry group switches off symmetrization.**

The **symmetry** group contains multiple **operator** groups. Each **operator** group contains the parameter **S**, a Cartesian rotation matrix given row-wise. The symmetries must form a group.

Example:

```
symmetry {
  // Symmetry Number 1, E
  operator { S = [[1.000000,0.000000,0.000000],
                 [0.000000,1.000000,0.000000],
                 [0.000000,0.000000,1.000000]]; }
  // Symmetry Number 2, m [0,0.707107,-0.707107]
  operator { S = [[1.000000,0.000000,0.000000],
                 [0.000000,0.000000,1.000000],
                 [0.000000,1.000000,0.000000]]; }
}
```

The best way to set up a reduced symmetry group is to use

```
sxstructsym --printsym -i input.sx
```

and then **grep** the symmetry group from the output and remove the unwanted symmetries.

3.2 The basis group

The **basis** group defines the plane-wave basis and the **k**-points, and optionally adjusts FFT mesh sizes.

Example:

```
basis {
  eCut = 20; // Ry
  kPoint {
    coords = [1/2,1/2,1/2];
    weight = 1;
    relative;
  }
  folding = 4 * [1,1,1];
}
```

The **basis** group must contain a **kPoint** (Monkhorst-Pack meshes) or a **kPoints** (bandstructures) group.

The following parameters may be set:

parameter	description
<code>eCut</code>	(required) Plane-wave cutoff for wavefunctions (in Rydberg)
<code>gCut</code>	(optional) Override cutoff for the density G-basis (defaults to $4 \times \text{eCut}$)
<code>folding</code>	Monkhorst-Pack folding. 3-vector of integers. Defaults to [1,1,1]
<code>mesh</code>	(optional) FFT mesh. 3-vector of integers. Default: automatic
<code>meshAccuracy</code>	(optional) FFT mesh accuracy, relative to the default. Default: 1, i.e. sufficient to hold $2 \times$ the wavefunction plane-waves to avoid wrap-around errors
<code>saveMemory</code>	(flag) Do not store phase-factor for each atom. This may make the code marginally slower, but save some RAM.

3.2.1 The `kPoint` group

The `kPoint` group defines the offset of the Monkhorst-Pack mesh. For this, one (or more) k-points are defined within the Brillouin zone. The complete zone with all the `k`-points in it (usually 1) is then shrunk by a factor `folding` in each direction; and the originally Brillouin zone is filled with copies of this shrunk zone. Afterwards, symmetry is used to remove redundant `k`-points.

Alternatively, all k-points can be specified via `kPoint` groups, assigning weights as desired.

Example:

```
kPoint { coords = [1/2, 1/2, 1/2]; relative; }
```

The following parameters may be set:

parameter	description
<code>relative</code>	(flag) Coordinates are relative. This should be usually set.
<code>coords</code>	(required) The coordinates. If relative flag is not given, the units are 1/bohr.
<code>weight</code>	(optional) Give a weight to this k-point. Weights must sum to 1. Default: 1/number of <code>k</code> -points.

Typical offsets are 0 or 1/2. For decoupling across vacuum regions with `folding=1`, use 1/4 to minimize band dispersion effects.

3.2.2 The `kPoints` group

The `kPoints` group is used to conveniently define band structure paths. It contains a sequence of `from` and `to` groups. **Note:** Band structure paths are subject to Monkhorst-Pack folding, so set `folding` to [1,1,1] or leave it out.

Example:

```

kPoints {
  dK = 0.01;
  // — fcc lattice
  // L point
  from { coords=PI/aLat * [1,1,1]; label="L"; }
  // Gamma point
  to { coords=[0,0,0]; label="\xG"; }
  // X point
  to { coords=[2 * PI/aLat, 0,0]; label="X"; }
}

```

The group must contain a **from**, and at least one **to** group.

The following parameters may be set:

parameter	description
relative	(flag) Coordinates are relative.
dK	(optional) Set the number of intermediate k -points such that the distance is at most dK (in 1/bohr).

3.2.3 The from group

The **from** group (within the **kPoints** group) adds a single **k**-point at the desired position. It may be used multiple times.

The following parameters may be set:

parameter	description
relative	(flag) Coordinates are relative.
coords	(required) The coordinates. If relative flag is not given, the units are 1/bohr.
label	(optional) String. Give a label to this k -point.

3.2.4 The to group

The **to** group (within the **kPoints** group) adds a line of **k**-points from the previous one to a new position. The number of points is set directly with **nPoints** or indirectly via **dK**.

The following parameters may be set:

parameter	description
relative	(flag) Coordinates are relative.
coords	(required) The coordinates. If relative flag is not given, the units are 1/bohr.
label	(optional) String. Give a label to this k -point.
dK	Set maximum k -point distance.
nPoints	Specify number of points to add. The final one will be at coords .

3.3 The pawPot group

The `pawPot` group defines the PAW potentials, by a sequence of `species` groups. The order of species must agree with the `structure` group.

Example:

```
pawPot {
  species {
    name = "Nitrogen ";
    potType = "AbInit ";
    element = "N";
    potential="N_LDA_abinit.paw ";
    lMaxRho=2;
    angularGrid=4;
  }
  species {
    name = "Hydrogen ";
    element="H ";
    ...
  }
}
```

The group must contain one `species` group per species. Within the `species` group, the following parameters are commonly set:

parameter	description
<code>name</code>	(required string) English name of the element
<code>element</code>	(optional string) Chemical symbol
<code>potential</code>	(required filename) Name of the potential file.
<code>potType</code>	(required string) Type of the potential file. May be "AbInit", "AtomPAW", "CPPAW", or "VASP".

The following parameters within the `species` group allow experimenting with some details.

parameter	description
<code>lMaxRho</code>	(optional) Truncate the spherical expansion of densities (and compensation charges) at this l .
<code>angularGrid</code>	(optional integer) Choose a different angular grid for xc calculation in the PAW sphere. Larger is finer. Default is 7 (110 points).
<code>nRadGrid</code>	(optional integer) Interpolate to a different radial grid.
<code>checkOverlap</code>	(flag) Check that PAW norm is guaranteed to be positive definite in the limit of large cutoffs. This is on by default. Some problematic PAW potentials may fail the check, but work normally in some circumstances, so you can switch off the check here.

3.4 The PAWHamiltonian group

The PAWHamiltonian group defines the DFT functional, the number of empty states, the Fermi smearing, and some other settings.

Example:

```
PAWHamiltonian {
  nEmptyStates = 10;
  ekt = 0.02;
  xc = LDA_PW;
}
```

The following common parameters may be set:

parameter	description
xc	(required) xc functional to be used. Constants are defined in <code>parameters.sx</code> . See below.
ekt	(optional) Fermi-Dirac smearing in eV. Should be 0 for semiconductors.
nEmptyStates	(optional) number of empty states. Remember to scale with system size! Defaults to zero, which is OK for semiconductors, and catastrophic for metals.
nExcessElectrons	(optional) Number of extra electrons (= minus charge). Can be fractional.
spinPolarized	(flag) Run a collinear spin-polarized calculation.
dipoleCorrection	(optional) Use the dipole correction for slab systems. The in-plane lattice must be perpendicular to the z-axis, and the third basis vector must be aligned with the z-axis. For charged calculation, this requests the generalized dipole correction, which may need some care for initializing the charge (see <code>charged</code> in the <code>initialGuess</code> group).
zField	(optional) Use an additional electric field along z when using the dipole correction (atomic units).

Available xc functionals The xc parameter can be LDA_PW (10), i.e. the Perdew-Wang parametrization of LDA, or PBE (1). Perdew-Zunger LDA (0) works, but is not recommended because the parametrization is discontinuous, limiting the convergence in some cases. If you need other functionals, contact freysoldt@mpie.de. Hybrid functionals are still experimental, and slow.

The following parameters allow experimenting with some details.

parameter	description
omegaHSE	(optional) Change the ω screening length of HSE
alphaHybrid	(optional) Change the non-local exchange mixing parameter of hybrid functionals.

The PAWHamiltonian group may additionally contain the vExt and xcMesh groups to set an external potential and the mesh for xc calculation, respectively.

3.4.1 The vExt group

The vExt group in the PAWHamiltonian or PWHamiltonian group defines an external potential.

Example:

```
PAWHamiltonian {
  ...
  vExt { file="sawtooth.sxb"; }
}
```

It contains a single parameter, `file`, which contains the filename of the netcdf-type potential file to be used. The format of that file is like for a density (see Sec. 6.4).

3.4.2 The xcMesh group

The xcMesh group defines a specific FFT mesh for the calculation of the xc functional. It may be set with either of the following parameters (cf. the mesh definition in the `basis` group). The default is to double the density mesh, roughly equivalent to `meshAccuracy=2`.

The xcMesh group may appear in some groups other than the Hamiltonian to temporarily override the xc mesh: `scfDiag.CCG`, `blockCCG`, `CCG`.

parameter	description
<code>eCut</code>	Plane-wave cutoff for wavefunctions (in Rydberg). The xc mesh will be sufficient to hold $2\times$ this cutoff.
<code>mesh</code>	FFT mesh. 3-vector of integers.
<code>meshAccuracy</code>	FFT mesh accuracy, relative to the default. Default: 1, i.e. sufficient to hold $2\times$ the wavefunction plane-waves to avoid wrap-around errors

3.5 The spinConstraint group

The optional `spinConstraint` group defines atomic spin constraints for PAW calculations. They can be set via atomic labels, or read in for all atoms from an external file.

Note: Atomic spins refer to the spin density inside the PAW cutoff sphere and are not identical to the definition used for setting up spin configurations from complete atoms in `initialGuess.atomicSpin`.

Example:

```

spinConstraint {
  label = "No.1 ";
  constraint = 2;
}
spinConstraint {
  label = "No.2 ";
  constraint = -2.5;
}

```

The following parameters may be set:

parameter	description
label	The present constraint applies to atoms with the given label.
constraint	Value of the desired atomic spin
file	Read all spin constraints from this file.

If the constraints are read from a file, there must be one number per atom. If not all atoms are constrained, the number is to be replaced by 'X', followed by a newline. For instance,

```

1
1
X
-2

```

for a four-atom calculation would constrain the spins of the first two atoms to a value of 1, the last one (no. 4) to a value of -2, and have no spin constraint on atom 3.

3.6 The initialGuess group

In order to start a DFT calculations, one must set up an initial guess for the density and for the wave functions. The `initialGuess` group defines how this is done, as well as a few other settings (such as keeping the waves on disk to save RAM).

Example:

```

initialGuess {
  waves { lcao {} }
  rho { atomicOrbitals; }
}

```

The default is to set up the density from a superposition of atomic densities, and the wave-functions from a single-step LCAO calculation, using the atomic valence orbitals [1]. This works exceptionally well. If you want to finetune the behavior, the `initialGuess` group must contain a `waves` or a `rho` group. Otherwise, you may omit the `waves` and `rho` groups to get the default behavior.

Additionally, the `initialGuess` group may contain an occupations group to set up initial occupations (notably when keeping them fixed), and an `exchange` group for hybrid functionals.

The following parameters may be set:

parameter	description
<code>noWavesStorage</code>	(flag) Do not save wavefunctions after the initial guess
<code>noRhoStorage</code>	(flag) Do not save the density after the initial guess.

3.6.1 The waves group

The `waves` group defines the strategy for setting up the initial waves. The major strategies are LCAO (best), reading from a file (excellent, if you have one), or random. To use LCAO, you must include an `lcao` group.

The following parameters may be set:

parameter	description
<code>file</code>	(optional) File name for reading in the initial guess from a previous calculation.
<code>random</code>	(flag) Initialize with random numbers.
<code>keepWavesOnDisk</code>	(flag) Keep waves on disk, load only a single k -point at each time. May save a lot of RAM, but can be quite a bottleneck on small systems.

3.6.2 The lcao group

The `lcao` group within the `initialGuess.waves` group finetunes the LCAO calculation, if necessary. Notably, you can iterate the LCAO calculation to self-consistency. This is generally **no good idea**.

parameter	description
<code>maxSteps</code>	(optional) Max. number of steps. If 0 or 1, the initial density will <i>not</i> be updated.
<code>dEnergy</code>	(optional) Energy convergence criterium

In addition to these, the `lcao` group supports all the mixer settings (`mixingMethod`, `nPulaySteps`, `spinMixing`, `rhoMixing`, `preconditioner` group) of the `scfDiag` group (Sec. 4.1).

3.6.3 The rho group

The `rho` group defines the strategy for the initial density. This can be a superposition of atomic densities, from a file, from the wave functions (if read from a file), or random.

The following parameters may be set:

parameter	description
<code>file</code>	Read density from this file.
<code>fromWaves</code>	(flag) Compute from the wave functions (which must be from file in this case).
<code>random</code>	(flag) Request random density
<code>atomicOrbitals</code>	(flag) Superposition of atomic densities
<code>spinMoment</code>	(optional) When from atomic densities, apply a global spin polarization.

If `atomicOrbitals` is chosen, one may set up a spin configuration by using `atomicSpin` groups.

For charged calculations, one may specify an initial localization of charge in the charged group.

3.6.4 The `atomicSpin` group

The `atomicSpin` group (within the `initialGuess.rho` group) defines spin polarization for the initial guess on an per-atom basis when the initial density is set up from atoms. Post-polarizing an external density is not possible at present. Atoms can be identified per label (one `atomicSpin` group per label), or from an external file with spins for all atoms.

Example:

```
aLat = 5.35;
structure {
  include <structures/sc.sx>;
  species { element="Fe";
    atom { coords=[0,0,0]; relative; label="A"; }
    atom { coords=[1/2, 1/2, 1/2]; relative;
      label="B"; }
  }
}
initialGuess {
  rho {
    atomicOrbitals;
    atomicSpin { label="A"; spin=2; }
    atomicSpin { label="B"; spin=-2; }
  }
}
```

The following parameters may be set:

parameter	description
<code>spin</code>	The desired spin moment value.
<code>label</code>	For which atoms does this spin apply?
<code>file</code>	(excludes spin and label) Read atomic spins from this file (one spin per line), one per atom, in sequential order.

3.6.5 The charged group

The `charged` group (within the `initialGuess.rho` group) defines the localization of initial charge. This may be a Gaussian charge, or a sheet-layer charge along z (for charged slabs) with a Gaussian profile.

Example:

```
initialGuess {
  rho {
    atomicOrbitals;
    charged { charge=1; coords=[0,0,13.2]; beta=2; }
  }
}
```

The following parameters may be set:

parameter	description
<code>charge</code>	(required) The classical charge (i.e. <code>-nExcessElectrons</code> from the <code>PAWHamiltonian</code> or <code>PWHamiltonian</code> group).
<code>beta</code>	(optional) Gaussian broadening
<code>z</code>	Request a sheet charge at this z
<code>coords</code>	Request a Gaussian charge at this position (in bohr).

Multiple charges can be set up. There is no check if the resulting density has the correct number of electrons.

3.6.6 The occupations group

The `occupations` group within the `initialGuess` group defines the initial occupations. This makes sense if the density is computed from wave functions, or if the occupations are going to be fixed at these values.

Example:

```
initialGuess {
  ...
  occupations {
    bands { range=[1,10]; focc=2; }
    kPoints { values=[1,3];
      bands { values=[10]; focc=0; }
      bands { values=[11]; focc=2; }
    }
  }
}
```

One can specify selected sets of states by nesting the following groups: `kPoints`, `spin`, `bands`. Each of these groups selects one or more indices (starting at 1) from the specified index type (i.e. `k`-points, spins, states) by one of the following two parameters:

parameter	description
values	(list of integers) Specifically list the indices affected.
range	(list of 2 integers) Specify start and end index.

The possible nestings are

- `kPoints { spin { bands { ... focc=...; } } }`
- `kPoints { bands { ... focc=...; } }`
- `spin { bands { ... focc= ...; } }`
- `bands { ... focc=...; }`

The innermost loop must set the `focc` parameter to the desired occupation. If an outer group is omitted, the settings apply to all indices of that type (e.g. no `kPoints` group = all `k`-points). The groups are processed in order of appearance, i.e., later groups override the previous settings, if the index ranges overlap.

In the above example, the first `bands` group sets the occupations of bands 1–10 at all `k`-points to 2. Then, we change the occupation at `k`-points 1 and 3, to have zero occupation in band 10 and an occupation of 2 for band 11.

3.6.7 The exchange group

Note: hybrid functionals are experimental and slow.

The `exchange` group allows to set waves for the non-local exchange operator at the initialization stage. This is necessary if you want to initialize the waves from an LCAO calculation. The exchange group contains a single parameter, `file`, which contains the filename of the waves file to be used.

Example:

```
initialGuess {
  exchange { file="waves-pbe.sxb"; }
  rho { file="rho-pbe.sxb"; }
  waves { lcao {} }
}
```

3.7 The pseudoPot group

The `pseudoPot` group defines the norm-conserving pseudopotentials by a sequence of species groups. The order of species must agree with the structure group.

Note: PAW and norm-conserving pseudopotentials cannot be mixed. Using `pseudoPot` requires to use `PWHamiltonian` to define the Hamiltonian.

Example:

```

pseudoPot {
  species {
    potential      = "al.cpi";
    name           = "Aluminum";
    element        = "Al";
    valenceCharge  = 3;
    lMax           = d;
    lLoc           = d;
    lcaoOrbitals   = [s,p,d];
    atomicRhoOcc   = [2,1,0];
    rGauss         = 1;
    reciprocalMass = 26.98;
    dampingMass    = 0.7;
    ionicMass      = 26.98;
  }
}

```

The group must contain one `species` group per species. Within the `species` group, the following parameters may be set:

parameter	description
<code>name</code>	(required string) English name of the element
<code>element</code>	(optional string) Chemical symbol
<code>potential</code>	(required filename) Name of the potential file.
<code>valenceCharge</code>	(required) Valence charge.
<code>lMax</code>	(required) Max. l-component of the pseudopotential.
<code>lLoc</code>	(required) Select the local l-component.
<code>lcaoOrbitals</code>	(required) Which orbitals should be used for lcao initialization. Note: <code>s,p,d</code> , and <code>f</code> are predefined constants in <code>parameters.sx</code> .
<code>rGauss</code>	(required) Broadening of compensation charge, usually 1.
<code>atomicRhoOcc</code>	(required) Occupation numbers for charge initialization.
<code>reciprocalMass</code>	(required) Mass of the ion.
<code>dampingMass</code>	(required, currently unused). Damping for damped-Newton geometry optimization.
<code>ionicMass</code>	(required) Mass of the ion.

Note: The appearance of two masses, as well as the lack of default parameters is a historic feature (mistake?) and may be changed in future versions.

3.8 The PWHamiltonian group

The PWHamiltonian group defines the DFT functional, the number of empty states, the Fermi smearing, and some other settings.

Example:

```

PWHamiltonian {
  nEmptyStates = 10;
  ekt = 0.02;
  xc = LDA;
}

```

The following common parameters may be set:

parameter	description
xc	(required) xc functional to be used. Constants are defined in <code>parameters.sx</code> . See below.
ekt	(optional) Fermi-Dirac smearing in eV. Should be 0 for semiconductors.
nEmptyStates	(optional) number of empty states. Remember to scale with system size! Defaults to zero, which is OK for semiconductors, and catastrophic for metals.
nExcessElectrons	(optional) Number of extra electrons (= minus charge). Can be fractional.
spinPolarized	(flag) Run a collinear spin-polarized calculation.
dipoleCorrection	(optional) Use the dipole correction for slab systems. The in-plane lattice must be perpendicular to the z-axis, and the third basis vector must be aligned with the z-axis. For charged calculation, this requests the generalized dipole correction, which may need some care for initializing the charge (see <code>charged</code> in the <code>initialGuess</code> group).
zField	(optional) Use an additional electric field along z when using the dipole correction (atomic units).

Available xc functionals The `xc` parameter can be `LDA_PW` (10), i.e. the Perdew-Wang parametrization of LDA, or `PBE` (1). Perdew-Zunger LDA (0) works, but is not recommended because the parametrization is discontinuous, limiting the convergence in some cases. If you need other functionals, contact freysoldt@mpie.de.

The `PWHamiltonian` group may additionally contain the `vExt` and `xcMesh` groups to set an external potential and the mesh for xc calculation, respectively.

3.9 The main group

The `main` group selects and controls the algorithms after startup during the main part of the calculation. It can be divided into two categories: electronic minimization (Sec. 4) and geometry optimization (Sec. 5). The `main` group can contain a single algorithm, or a sequence of them, which are then executed in order of appearance.

All self-consistent DFT calculations must employ some algorithm to compute the electronic wavefunctions and density for a given geometric structure. If

additionally the atomic positions are altered according to the calculated forces, electronic minimization becomes the inner loop. Consequently, the electronic minimizers appear in the `bornOppenheimer` group of the geometry optimizers. Electronic minimizers may appear as a direct subgroup of `main`. It may sometimes be useful to select a different set of electronic minimization settings for the initial phase, if the initial guess is not good enough, and then use other settings (less robust, more efficient) later on.

Example:

```

main {
  // — get a better starting guess with
  //    small rhoMixing
  scfDiag {
    dEnergy=1e-4;
    rhoMixing=0.3;
    maxSteps=100;
  }
  // — optimize geometry
  linQN {
    dEnergy = 1e-6;
    maxSteps=50;
    bornOppenheimer {
      scfDiag {
        dEnergy = 1e-8;
        rhoMixing=1;
      }
    }
  }
}

```

The group must contain one or more electronic minimizer (`scfDiag`, `CCG`) or geometry optimizer (`QN`, `linQN`, `ricQN`) group.

The main group has no parameters of its own.

4 Electronic loop

4.1 `scfDiag`: iterative diagonalization + density mixing

The `scfDiag` group selects and controls the iterative diagonalization + density mixing algorithm for the solution of the Kohn-Sham DFT equations.

Example:

```

scfDiag {
  blockCCG { blockSize=32; maxStepsCCG=4; }
  dEnergy = 1e-7;
  preconditioner { type=KERKER; scaling=1;
                    kerkerDamping=1; }
  mixingMethod = PULAY;
  nPulaySteps = 7;
}

```

The group must contain one of the iterative diagonalization groups: CCG (conjugate-gradient³), **blockCCG** (block conjugate-gradient, recommended). It may contain a **xcMesh** group (to override the xc mesh) and a **preconditioner** group (for the density). If the density preconditioner is not specified, Kerker preconditioning with a default damping is used.

The following parameters may be set:

³The first C stands for *Complex*.

parameter	description
dEnergy	(optional) Free energy convergence criterium (in Hartree). Default is 10^{-8} .
maxSteps	(optional) Max. number of steps (density updates).
maxResidue	(optional) Additional requirement for convergence: density residue must fall below this threshold.
printSteps	(optional) Eigenvalues are printed by default every 10 steps. This interval can be changed by printSteps .
mixingMethod	(optional) Method for the density mixing. Constants defined in parameters.sx . Can be PULAY (default, 2) or LINEAR (0).
nPulaySteps	(optional) Number of previous steps (densities) to use in Pulay mixing. Default: 7.
rhoMixing	(optional) Additional linear mixing factor for density updates (1=full update (default), 0=no change). Low values may lead to a more stable convergence, but will slow down the calculation if set too low.
spinMixing	(optional) Linear mixing parameter for spin densities.
keepRhoFixed	(flag) Do not update the density (for band structures).
keepOccFixed	(flag) Do not update the occupation numbers.
keepSpinFixed	(flag) Do not change the spin moment.
spinMoment	(optional) Keep the spin moment at this value.
ekt	(optional) Override electronic temperature setting in the Hamiltonian group.
dipoleCorrection	(flag) Override the dipole correction setting in the Hamiltonian group.
dSpinMoment	accuracy of iterative enforcement of spin constraints. Default: 10^{-8} .
noRhoStorage	(flag) Do not write rho.sxb .
noWavesStorage	(flag) Do not write waves.sxb .

Multiple iterative diagonalizer groups may be used to change the xc mesh during the minimization. For this, each diagonalizer groups must contain the **dEnergy** parameter. **Example:**

```

scfDiag {
  blockCCG { xcMesh { meshAccuracy=0.7; }
                dEnergy=1e-4; }
  blockCCG { xcMesh { meshAccuracy=1; }
                dEnergy=1e-8; }
  blockCCG { xcMesh { meshAccuracy=2; }
                dEnergy=1e-9; }
  dEnergy=1e-9;
}

```

This example would use an xc-mesh with a relative accuracy of 0.7 until the energy has converged to 10^{-4} Hartree, a standard $2\times$ mesh (accuracy=1) until

the energy change is below 10^{-8} Hartree, and a double-accuracy mesh thereafter. The following parameters allow messing around with some details.

parameter	description
<code>dRelRes</code>	(optional) The energy convergence criterium for eigenvalues is calculated from the density residue adaptively. This parameter allows to set the initial (and maximum) value of the scaling factor.
<code>calcForces</code>	(flag) Calculate and print forces in each step (slow!). This can be used to determine the influence of convergence criteria on the precision in forces.
<code>dumpTime</code>	(optional) Set interval between dumps of density/wave functions. The dumps may allow for restarts when a calculation crashes. Since the dumping happens at the end of a SCF cycle, the actual dumping intervals may be longer. Default: 12 hours.

4.1.1 The CCG group

The CCG group (within the `scfDiag` group) selects conjugate-gradient algorithm for (inner-loop) iterative diagonalization. After all states have been updated, a subspace diagonalization is performed. This algorithm works best for very small systems. For larger systems (> 5 states), the `blockCCG` is superior.

Note: CCG is also the name for the conjugate-gradient-based direct minimization algorithm, see Sec. 4.2.

The following parameters may be set:

parameter	description
<code>dRelEps</code>	(optional) Stop iterating when the change in eigenvalue falls below this fraction of the change in the first (steepest-descent) step.
<code>maxStepsCCG</code>	(optional) Max. number of steps to perform. Default: 5.
<code>dEnergy</code>	(optional) Use these settings until energy change fall below this threshold.

The CCG group may contain a `xcMesh` group to override the xc mesh settings from the Hamiltonian or the `scfDiag` group.

4.1.2 The blockCCG group

The `blockCCG` group (within the `scfDiag` group) selects the block conjugate-gradient algorithm for (inner-loop) iterative diagonalization. After all states have been updated, a subspace diagonalization is performed. For very small systems (≤ 5 states), the unblocked CCG is superior.

The following parameters may be set:

parameter	description
<code>dRelEps</code>	(optional) Stop iterating when the change in eigenvalue falls below this fraction of the change in the first (steepest-descent) step.
<code>maxStepsCCG</code>	(optional) Max. number of steps to perform. Default: 5.
<code>blockSize</code>	(optional) Block size. Default: 64
<code>nSloppy</code>	(optional) Don't try to converge the highest nSloppy states (useful for bandstructures).
<code>dEnergy</code>	(optional) Use these settings until energy change fall below this threshold.
<code>verbose</code>	(flag) Produce debug output.
<code>numericalLimit</code>	(flag) Stop iterating when approaching the numerical limit.

The `blockCCG` group may contain a `xcMesh` group to override the keyxc mesh settings from the Hamiltonian or the `scfDiag` group.

4.1.3 The preconditioner group

The `preconditioner` group defines the density preconditioner, i.e., a transformation of the observed (or predicted) difference between the input and output density to the applied changes to the input density. An ideal preconditioner models the screening behavior of the system and is able to include the expected screening response into the suggested density change. Selecting an appropriate preconditioner, that reflects the screening properties of the system at hand, is a key to an efficient (i.e. fast) convergence. The preconditioner does *not* affect the converged result.

The following parameters may be set:

parameter	description
<code>type</code>	(required) Type of preconditioner, see below
<code>scaling</code>	(optional) Additional scaling factor. Default 1.
<code>spinScaling</code>	(optional) Additional scaling factor for the spin density. Default 1.
<code>kerkerDamping</code>	(optional) Damping constant for Kerker preconditioner. Default: 0.6
<code>dielecConstant</code>	(optional) Dielectric constant for the CSR model.

The following preconditioner types are available (constants defined in `parameters.sx`).

- NONE (0). No preconditioning. Ideal for atoms/molecules in vacuum.
- KERKER (1). Kerker preconditioner. Ideal for metals.
- CSR (3). Preconditioner for semiconductors based on the Cappellini-del-Sole-Reining-Bechstedt model dielectric function. Requires `dielecConstant`.
- ELLIPTIC (5). An explicit-solver preconditioner. No screening in vacuum region, Thomas-Fermi screening (Kerker-like) elsewhere. Ideal for metallic

slabs.

4.2 CCG: direct minimization

The CCG group selects and controls the direct minimization algorithm for the solution of the Kohn-Sham DFT equations [2].

Example:

```
CCG {  
  dEnergy=1e-7;  
  finalDiag;  
}
```

It may contain a `xcMesh` group to override the xc mesh settings from the Hamiltonian group.

The following parameters may be set:

parameter	description
<code>dEnergy</code>	(optional) Free energy convergence criterium (in Hartree). Default is 10^{-8} .
<code>maxSteps</code>	(optional) Max. number of steps.
<code>printSteps</code>	(optional) Eigenvalues are printed by default every 10 steps. This interval can be changed by <code>printSteps</code> .
<code>initialDiag</code>	(flag) Perform iterative wave-function optimization based on the initial density (this is the default)
<code>finalDiag</code>	(flag) Perform subspace diagonalization at the end.
<code>kappa</code>	(optional) Initial mixing between subspace Hamiltonian and wave-function updates. If set to a negative value, the value of κ will be fixed at the absolute value. Otherwise, κ is adapted on the fly.
<code>keepOccFixed</code>	(flag) Do not update the occupation numbers.
<code>ekt</code>	(optional) Override electronic temperature setting in the Hamiltonian group.
<code>dipoleCorrection</code>	(flag) Override the dipole correction setting in the Hamiltonian group.
<code>noRhoStorage</code>	(flag) Do not write <code>rho.sxb</code> .
<code>noWavesStorage</code>	(flag) Do not write <code>waves.sxb</code>

Note about switching between `scfDiag` and CCG: The direct minimization algorithm requires a good initial guess for the wave functions. Therefore, the default is to run a iterative diagonalization (blockCGG algorithm) before starting direct minimization. This is unnecessary when the wavefunctions come from iterative diagonalization, and can be switched off via the `initialDiag` flag. For semiconductors with no empty states, on the other hand, the wavefunctions spanning the occupied subspace may not be diagonalizing the Hamiltonian. In order to switch to `scfDiag` or to obtain eigenvalues, the `finalDiag` flag must

be set. If partially occupied or empty states are computed, an approximate diagonalization takes place as part of the algorithm.

5 Geometry optimizers

This section describes the geometry optimization groups. We have experimented with geometry optimization and found BFGS quasi-Newton schemes to be most efficient. Therefore, you will see three quasi-Newton optimizers. For small systems, the performance is quite similar. For more complex systems, the `ricQN` variant is recommended.

In addition to the geometry optimizers, there is a pseudo-optimizer `extControl`. This algorithm opens two communication channels (named pipes) and allows to control geometry updates (and other things) from external scripts.

In all cases, the inner electronic loop enjoys the same flexibility of sequencing as the `main` group. Therefore, each geometry optimizer group contains a `bornOppenheimer` group that contains one or more electronic minimizers.

5.1 The QN group

The `QN` group selects and controls the geometry optimization via quasi-Newton scheme with BFGS updates. **Note:** In general, `ricQN` is the faster algorithm.

Example:

```
QN {
  maxSteps = 20;
  dEnergy = 1e-5;
  dF = 1e-3;
  maxStepLength=0.2;
  bornOppenheimer {
    scfDiag {
      maxSteps = 50;
      blockCCG { }
      dEnergy = 1e-7;
    }
  }
}
```

The group must contain a `bornOppenheimer` group to specify the electronic loop.

The following parameters may be set:

parameter	description
<code>maxSteps</code>	(optional) max. number of steps, default: 50
<code>dX</code>	(optional) convergence reached only when maximum displacement (length of displacement vector of a single atom) is less than this value (in bohr). Default: 0.01
<code>dF</code>	(optional) convergence reached only when maximum force (length of force vector of a single atom) is less than this value (in Hartree/bohr). Default: 0.001
<code>dEnergy</code>	(optional) convergence reached only when change in energy is less than this value (in Hartree). Default: 10^{-4}
<code>maxStepLength</code>	maximum allowed displacement (length of displacement vector for a single atom) in bohr. Larger steps are reduced by scaling. Default: 0.3
<code>hessian</code>	(filename) Initialize Hessian from file.
<code>driftFilter</code>	(flag) Project out the average force and displacement. Default: yes, if no constraints are used.

5.1.1 The `bornOppenheimer` group

The `bornOppenheimer` group defines the electronic loop within a geometry optimization. It contains one or more of the electronic loop groups, see Sec. 4. If more than one minimizer is used, the complete electronic loop sequence is executed at each ionic step.

5.2 The `linQN` group

The `linQN` group selects and controls the geometry optimization via quasi-Newton scheme with BFGS updates for the inverse Hessian. **Note:** In general, `ricQN` is the faster algorithm.

Example:

```

linQN {
  maxSteps = 20;
  dEnergy = 1e-5;
  dF = 1e-3;
  maxStepLength=0.2;
  bornOppenheimer {
    scfDiag {
      maxSteps = 50;
      blockCCG { }
      dEnergy = 1e-7;
    }
  }
}

```

The group must contain a `bornOppenheimer` group to specify the electronic loop.

The following parameters may be set:

parameter	description
<code>maxSteps</code>	(optional) max. number of steps, default: 50
<code>dX</code>	(optional) convergence reached only when maximum displacement (length of displacement vector of a single atom) is less than this value (in bohr). Default: 0.01
<code>dF</code>	(optional) convergence reached only when maximum force (length of force vector of a single atom) is less than this value (in Hartree/bohr). Default: 0.001
<code>dEnergy</code>	(optional) convergence reached only when change in energy is less than this value (in Hartree). Default: 10^{-4}
<code>maxStepLength</code>	maximum allowed displacement (length of displacement vector for a single atom) in bohr. Larger steps are reduced by scaling. Default: 0.3
<code>nProjectors</code>	(optional) number of previous steps to use for BFGS updates. Default: 10
<code>hessian</code>	(filename) Initialize Hessian from file.
<code>driftFilter</code>	(flag) Project out the average force and displacement. Default: yes, if no constraints are used.

5.3 The `ricQN` group

The `ricQN` group requests a quasi-Newton optimization with BFGS updates [3] of an on-the-fly optimized internal-coordinate based initial guess for the Hessian.

The following parameters may be set:

parameter	description
maxSteps	(optional) max. number of steps, default: 50
dX	(optional) convergence reached only when maximum displacement (length of displacement vector of a single atom) is less than this value (in bohr). Default: 0.01
dF	(optional) convergence reached only when maximum force (length of force vector of a single atom) is less than this value (in Hartree/bohr). Default: 0.001
dEnergy	(optional) convergence reached only when change in energy is less than this value (in Hartree). Default: 10^{-4}
nProjectors	(optional) number of previous steps to use for BFGS updates. Default: 10
maxStepLength	maximum allowed displacement (length of displacement vector for a single atom) in bohr. Larger steps are reduced by the trust radius method to a value close to the maximum (within 1%). Default: 0.3
softModeDamping	(optional) Initial value for Hessian shift (in Hartree/bohr ²). This is overridden with the first successful fit of a positive shift parameter. Default: 1e-2.
driftFilter	(flag) Project out the average force and displacement. Default: yes, if no constraints are used.

The group must contain a `bornOppenheimer` group to specify the electronic loop. The `ricQN` group may contain a `ric` group (see Sec. 5.3.1 to define the internal coordinate generation. If left out, default parameters are used, and output from the internal coordinate setup is suppressed.

5.3.1 The `ric` group

The `ric` group defines the parameters for internal coordinate generation.

The following parameters may be set:

parameter	description
<code>maxDist</code>	maximum possible distance for considering neighbors (in bohr). Default: 10
<code>typifyThreshold</code>	minimum bond length separation of distinct bond types (the <i>f</i> parameter in [3]). After sorting the bond lengths, the logarithm of subsequent lengths are compared. If they differ by less than the threshold, the two bonds are assigned the same bond type. Default: 0.05
<code>rmsThreshold</code>	minimum distance between two bond length clusters in units of their root-mean-square displacements (the <i>R</i> parameter of [3]). Default: 3
<code>planeCutLimit</code>	Relative size of coordination polyhedra to separate the nearest neighbors from further atoms (the <i>P</i> parameter of [3]). Larger values allow for more neighbors. Default: 0.95
<code>withAngles</code> <code>bvkAtoms</code>	(flag) add bond angle coordinates for all bonds (optional, experimental) List of atom ids (starting from 1) for which born-von-Karman transversal force constants are added. The comma-separated list must be enclosed by square brackets []. This adds a bond-directional coordinate to each bond of the atoms in the list.

5.4 The `extControl` group

The `extControl` group allows to control parts of the SPHInX run by external scripts. For this, two communication channels are opened. Typically, these will be named pipes. For more info on the concept, see the `extControl` group is the ‘DFT code’ side of the atomic structure algorithm protocol (ASAP).

The names of the communication files are specified via the environment, in `SX_EXT_CTRL` and `SX_EXT_RES`, respectively.

The group must contain one or more `bornOppenheimer` groups. Each `bornOppenheimer` group may contain an `id` parameter that allows to run the specified sequence of electronic minimizers (usually one) with the `run` command (see below).

If forces are not needed, the `noForces` flag can be used to suppress the calculation of forces.

The `extControl` algorithm understands the following commands:

command	description
<code>confirm y</code>	Confirm <i>ASAP</i> commands
<code>confirm n</code>	Do not confirm <i>ASAP</i> commands
<code>end</code>	End the calculation
<code>run [<id>]</code>	Run specified bornOppenheimer group (first one, if <id> is omitted).
<code>onproblem=crash</code>	Crash on wrong commands
<code>onproblem=stop</code>	Stop on wrong commands
<code>onproblem=ignore</code>	Ignore wrong commands (default)
<code>get energy</code>	Print free energy on result channel
<code>get forces</code>	Print forces on result channel
<code>get natoms</code>	Print number of atoms on result channel
<code>get nspecies</code>	Print number of species, and for each species number of atoms on result channel
<code>get structure</code>	Print atomic coordinates on result channel
<code>get positions</code>	Print atomic coordinates + chemical symbol on result channel
<code>get cell</code>	Print unit cell on result channel
<code>set structure</code>	Set atomic coordinates
<code>set positions</code>	Set atomic coordinates
<code>shift atom</code>	<id> <dx> <dy> <dz> shift specified atom. id starts at 1 and enumerates atoms across all species.
<code>set cell</code>	<i>not supported</i>
<code>get stress</code>	<i>not supported</i>
<code>get elements</code>	Print chemical symbols on result channel
<code>get nspinconstraints</code>	Print number of spin constraints on result channel
<code>get nu</code>	Print spin constraint Langrange parameters on result channel
<code>set spinconstraint</code>	Set target spins for spin constraints
<code>get spinconstraint</code>	Print target spins for spin constraints on result channel
<code>get atom spin</code>	Print atomic spins on result channel
<code>enable spinconstraint</code>	Switch on spin constraint
<code>disable spinconstraint</code>	Switch off spin constraint

6 Output

6.1 energy.dat: total energies

This file lists the total energies in each electronic step. The format for `scfDiag` is

```
<step> <accumulated time> <total energy> <band energy>
```

Units are Hartree.

Note: The energy printed is the finite-temperature total energy, not the free energy and not the T=0K extrapolated one.

The format for CCG is

```
<step> <accumulated time> <total energy> <free energy>
```

Units are Hartree.

6.2 residue.dat: density residues

This file contains the density residue for each electronic step. The format is

```
<step> <residue>
```

For spin-polarized calculations, the third column lists the residue of the spin density.

6.3 eps.dat: eigenvalues

This file contains the computed eigenvalues. The format is

```
<ik> <eps_1> <eps_2> <eps_3> ...
```

Units are eV.

6.4 rho.sxb: density (binary)

This file contains the final density in netcdf-format. The mesh order is z running fastest. For details on how to interpret the variables, please contact me.

6.5 waves.sxb: wave functions (binary)

This file contains the final wave functions in netcdf-format. It's pointless to try to process this file outside the SPHInX library. Several add-ons are available for processing the wavefunctions.

6.6 relaxedStr.sx: final atomic structure

This file lists the final atomic positions in SPHInX format. If the optimization does not converge, it contains the last configuration calculated.

6.7 relaxHist.sx: geometry optimization history

This file lists for each calculated configuration the atomic positions and forces, in SPHInX format.

6.8 energy-structOpt.dat: geometry optimization energies

This file lists for each step the energy. The format is one step per line:

```
<it> <energy (in Hartree)>
```

The 0-th step is the initial structure.

6.9 `ftwisdom.dat`: FFTW plans

FFTW wisdom file. May be used to speed up FFTW planning in add-ons.

References

- [1] J. Neugebauer and C. G. Van de Walle, in *Materials Theory, Simulations, and Parallel Algorithms, MRS Symposia Proceedings*, edited by E. Kaxiras, J. Joannopoulos, P. Vashisha, and R. K. Kalia (MRS, Pittsburgh, 1996), vol. 408.
- [2] J. N. C. Freysoldt, S. Boeck, Phys. Rev. B **79**, 241103(R) (2009).
- [3] C. Freysoldt, Comp. Mat. Sci. **133**, 71 (2017).

Index

- alphaHybrid, 13
- angular grid, 12
- angularGrid, 12
- ASAP, 32
- atom, 8
 - definition, 8
- atomic positions, 6–8
- atomic structure, 6
- atomic structure algorithm protocol, 32
- atomicOrbitals, 17
- atomicRhoOcc, 20
- atomicSpin, 14, 17
 - definition, 17

- band structure path, 10
- basis, 6, 14
 - definition, 9
- beta, 18
- blockCCG, 14, 23, 25
 - definition, 25
- blockSize, 26
- bornOppenheimer, 22, 28, 30–32
 - definition, 29
- bvkAtoms, 32

- calcForces, 25
- CCG, 14, 22, 23, 25, 34
 - definition, 25, 27
- charge, 13, 18, 21
- charge, 18
- charged, 13, 17, 21
 - definition, 18
- checkOverlap, 12
- chemical element, 12, 20
- comment, 4
- conjugate-gradient, 25
- constraint, 15
- convergence, 29–31
 - density residue, 24
 - energy, 16, 24, 27
- coords, 8, 10, 11, 18
- CSRB, 26
- cutoff, 10

- dampingMass, 20
- dEnergy, 16, 24–27, 29–31
- density preconditioner, 26
- dF, 29–31
- diagonalization, 22, 23, 25
- dielecConstant, 26
- dipole correction, 13, 21, 24
- dipoleCorrection, 13, 21, 24, 27
- direct minimization, 27
- dK, 11
- dRelEps, 25, 26
- dRelRes, 25
- driftFilter, 29–31
- dSpinMoment, 24
- dumping interval, 25
- dumpTime, 25
- dX, 29–31

- eCut, 10, 14
- ekt, 13, 21, 24, 27
- electric field, 13
- electronic minimizer, 22
- electronic temperature, 24, 27
- element, 12, 20
- element, 8, 12, 20
- empty states, 13, 21
- energy convergence, 16, 24, 27
- energy-structOpt.dat, 34
- energy.dat, 33
- eps.dat, 34
- exchange, 16
 - definition, 19
- extControl, 28
 - definition, 32
- external potential, 14

- Fermi-Dirac smearing, 13, 21
- FFT mesh, 9, 10, 14
 - xc computation, 14
- fftwisdom.dat, 35
- file, 14–17, 19
- finalDiag, 27
- flag, 4

focc, 19
 folding, 10
 format, 5
 from, 10, 11
 definition, 11
 fromWaves, 17
 functional, 13, 20

 gCut, 10
 geometry
 input, 6
 optimization, 28

 hessian, 29, 30

 id, 32
 initial guess, 15
 initialDiag, 27
 initialGuess, 6, 13, 14, 16–18, 21
 definition, 15
 input file, 3
 comment, 4
 expression, 5
 flag, 4
 format, 4
 internal coordinate, 31
 ionicMass, 20

 kappa, 27
 keepOccFixed, 24, 27
 keepRhoFixed, 24
 keepSpinFixed, 24
 keepWavesOnDisk, 16
 Kerker, 26
 kerkerDamping, 26
 kPoint, 9
 definition, 10
 kPoints, 9, 11
 definition, 10

 label, 8, 11, 15, 17
 LCAO, 15, 16, 19
 lcao, 16
 definition, 16
 lcaoOrbitals, 20
 LDA, 13, 21
 linQN, 22
 definition, 29
 lLoc, 20
 lMax, 20
 lMaxRho, 12

 main, 6, 28
 definition, 21
 maxDist, 32
 maxResidue, 24
 maxStepLength, 29–31
 maxSteps, 16, 24, 27, 29–31
 maxStepsCCG, 25, 26
 memory
 save, 10, 15
 mesh, 10, 14
 meshAccuracy, 10, 14
 mixer, 16
 mixing, 24
 mixingMethod, 24
 Monkhorst-Pack, 9, 10
 movable, 7, 8
 movableLine, 8
 movableX, 7, 8
 movableY, 7, 8
 movableZ, 7, 8

 name, 12, 20
 nEmptyStates, 13, 21
 nExcessElectrons, 13, 21
 noForces, 32
 noRhoStorage, 16, 24, 27
 norm-conserving pseudopotentials, 19
 noWavesStorage, 16, 24, 27
 nPoints, 11
 nProjectors, 30, 31
 nPulaySteps, 24
 nRadGrid, 12
 nSloppy, 26
 numericalLimit, 26

 occupation, 18
 fixed, 24, 27
 occupations
 definition, 18
 omegaHSE, 13
 operator, 9

- parameter.sx
 - location, 5
- parameters.sx, 5, 13, 20, 21, 24, 26
- PAW potentials, 12
- PAWHamiltonian, 6, 14, 18
 - definition, 13
- pawPot, 6
 - definition, 12
- PBE, 13, 21
- plane-wave basis, 9
- plane-wave cutoff, 10
- planeCutLimit, 32
- potential
 - norm-conserving, 19
- potential, 12, 20
- potType, 12
- preconditioner, 26
- preconditioner, 16, 23
 - definition, 26
- printSteps, 24, 27
- pseudoPot, 6
 - definition, 19
- Pulay mixing, 24
- PWHamiltonian, 6, 14, 18, 19
 - definition, 20
- QN, 22
 - definition, 28
- radial grid, 12
- RAM
 - save, 10, 15
- random, 16, 17
- range, 19
- range limits, 5
- reciprocalMass, 20
- relative, 8, 10, 11
- relaxedStr.sx, 34
- relaxHist.sx, 34
- residue.dat, 34
- rGauss, 20
- rho, 15, 17, 18
 - definition, 16
- rho.sxb, 24, 27, 34
- rhoMixing, 24
- ric, 31
 - definition, 31
- ricQN, 22, 28, 29
 - definition, 30
- rmsThreshold, 32
- S, 9
- saveMemory, 10
- scaling, 26
- scfDiag, 14, 16, 22, 25–27, 33
 - definition, 22
- slab, 13, 21
- softModeDamping, 31
- species, 7, 12, 20
 - definition, 7
- spin, 13
 - fixed, 24
- spin, 17
- spin configuration, 17
- spin constraints, 14, 24
- spin polarization, 17
- spin-polarized, 13, 21
- spinConstraint
 - definition, 14
- spinMixing, 24
- spinMoment, 17, 24
- spinPolarized, 13, 21
- spinScaling, 26
- std, 5
- steps, 24, 27
- structure, 6, 12
 - definition, 6
- subspace diagonalization, 25, 27
- SX_EXT_CTRL, 32
- SX_EXT_RES, 32
- symmetry, 7
 - definition, 8
- symmetry group, 9
- to, 10, 11
 - definition, 11
- type, 26
- typifyThreshold, 32
- units, 3
- valenceCharge, 20

values, 19
verbose, 26
vExt, 14, 21
 definition, 14

waves, 15, 16
 definition, 16
waves.sxb, 24, 27, 34
weight, 10
withAngles, 32

xc, 13, 21
xc functional, 13, 21
xc mesh, 23, 25, 27
xcMesh, 14, 21, 23, 25–27
 definition, 14

z, 18
zField, 13, 21